

SAFEX® -NEBELGERÄT

Fog Generator

PROTECTOR SERIE II

Technische Daten - *Technical data (Stand 7.03)*

Special fog generator designed for modern bugler alarm systems. The machine covers the protected area so fast with thick Fog, that any intruder is immediately stopped.

With two fog outlets and direct able nozzles a wide area can be protected. Equipped with several safety devices, self protecting alarm contacts, the machine can be on duty 24 h a day.

The generator is also available in a slightly modified version for the use in the field of entertainment where a high fog output in short time is required.



Elektrische Kenndaten:

Electrical data:

230 Volt AC / 50 Hz – 1500 W – Sicherung: 10 Amp. -mittelträge

230 Volt AC / 50 Hz – 1500 W – Fuse: 10 Amp. -semi time-lag)

Länge:

Length:

435 mm

Breite:

Width:

243 mm

Höhe:

Height:

246 mm

Gewicht:

Weight:

21,1 kg

Tank:

Tank:

1,7 Liter, extern beliebig – 1,7 litres, external unrestricted

Aufheizzeit:

Heating up time:

ca. 30 Minuten - approx. 30 minutes

Wiederaufheizzeit:

Reheating time:

ca. 13 Minuten - approx. 13 minutes

Nebelfluidverbrauch:

Fog fluid consumption:

max. 430 ml/min.

Nebelerzeugung:

Fogging power

ca. 4500 cbm (Sichtweite von 0,5 mtr. in einem Raum von 5 x 8 x 2,5 mtr.)

approx. 4500 m³ (visibility of 0,5 m in a room of 5 x 8 x 2,5 m)

Fernsteueranschluß:

Remote control:

230 Volt – 8-polige Fernsteuer-Dose aus GFK

8-pole remote control socket

Zubehör:

Accessories:

3 m. Gummi-Netzkabel, Ansaugschlauch und Filter, Gebrauchsanweisung,

Tankdeckel (Kanister) mit Ansaugschlauch

3 m flexible power cord, tank holder, suction hose and filter, instruction manual,

external tank lid (canister) with suction hose

Sonderzubehör:

Optional accessories:

Nebeldüsen - fog nozzles

Nebelflüssigkeit:

Fog fluid:

Alle SAFEX®-INSIDE-NEBEL Fluide (Nach DIN/VDE 0700 Teil 245 # 32.1)

All SAFEX®-INSIDE-FOG- fluids (According to DIN/VDE 0700 part 245 # 32.1)